

722-239

SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|--|---|------------------|
| DC Voltage | 200mV/2000mV/20V/200V/500V | $\pm (0.5\%+2)$ |
| AC Voltage | 200V/500V | $\pm (1.2\%+10)$ |
| DC Current | 2000 μ A/20mA/200mA/10A | $\pm (1\%+2)$ |
| Resistance | 200 Ω /2000 Ω /20k Ω /200k Ω /20M Ω /200M Ω | $\pm (0.8\%+2)$ |
| Special Functions | | |
| Diode | ✓ | |
| Continuity Buzzer | ✓ | |
| Square Wave Output | ✓ | |
| Data Hold | ✓ | |
| Display Backlight | ✓ | |
| Low Battery Display | ✓ | |
| Input Impedance for DC Voltage Measurement | Around 10M Ω | |
| Max. Display | 1999 | |

GENERAL CHARACTERISTICS

| | |
|------------------------------|--|
| Power | 9V Battery (6F22) |
| LCD Size | 48 x 16mm |
| Product Colour | Red and Grey |
| Product Net Weight | Around 156g |
| Product Size | 130 x 73.5 x 35mm |
| Standard Accessories | Test Lead, Battery, English Manual, Holster |
| Optional Accessories* | Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2) |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 60 pcs |
| Standard Carton Measurement | Around 486 x 345 x 310 mm (Around 0.052 CBM Per Standard Carton) |
| Standard Carton Gross Weight | Around 18kg |